



**Industrial-Maid**  
351 S. 12th Rd.  
Cortland, Nebraska 68331

**TF: 1-877-624-3247**  
**Fax: 402-798-7117**  
**www.industrial-maid.com**

### FR Cell/Poly Blend Cartridge

Industrial Maid’s filters are made from a premium blend of flame retardant cellulose and polyester. This material is especially designed for back pulse operations, and offers enhanced stability and structural integrity. All cellulose blend filters are dimpled pleated. This pleat lock helps maintain pleat spacing during operation.



Height:	19.5"
Outside Diameter:	17.25"
Inside Diameter:	12.75"
Style:	Open/Open
Gasket:	NG-14
Pleat Count:	450
Pleat Depth:	2"
Pleat Spacing:	Pleat lock
Filtration Area:	250
Filter Media:	FR Cell/Poly Blend
Inner Cage:	Galv. Expanded Metal 72% Open
Outer Cage:	Galv. Expanded Metal 72% Open
End Caps:	Galvanized Metal
Pleat/End Cap Bonding:	Urethane
Nominal Air Flow:	500 cfm
Nominal Resistance:	1.0" wg
Efficiency:	99.5 @ .5 micron
Max. Operating Temp:	180°F
Shipping Weight	21 lbs

