



Industrial-Maid  
351 S. 12th Rd.  
Cortland, Nebraska 68331

TF: 1-877-624-3247  
Fax: 402-798-7117  
www.industrial-maid.com

TD1915526100-32535/8PP-32535-00

### FR Cell/Poly Blend Cartridge

Industrial Maid's filters are made from a premium blend of flame retardant cellulose and polyester media. This material is especially designed for back pulse operations, and offers enhanced stability and structural integrity. All cellulose blend filters are dimpled pleated. This pleat lock helps maintain pleat spacing during operation.



Height:	26"
Outside Diameter:	13.865"
Inside Diameter:	9.479"
Style:	Open on Both Ends
Gasket:	.5" x .5" Molded Natural Rubber
Pleat Count:	355
Pleat Depth:	2"
Pleat Spacing:	Pleat lock
Filtration Area:	256 Sqft
Filter Media:	FR Cell/Poly Blend
Inner Cage:	Galv. Expanded Metal 72% Open
Outer Cage:	Galv. Expanded Metal 72% Open
End Caps:	Galvanized Metal
Pleat/End Cap Bonding:	Urethane
Nominal Air Flow:	500 cfm
Nominal Resistance:	1.0" wg
Efficiency:	99% @ .5 micron
Max. Operating Temp:	180°F



1915526100

