



Industrial-Maid
351 S. 12th Rd.
Cortland, Nebraska 68331

TF: 1-877-624-3247
Fax: 402-798-7117
www.industrial-maid.com

TD1915526100-42058/8PP-42058-00

FR Cell/Poly Blend Cartridge

Industrial Maid's filters are made from a premium blend of flame retardant cellulose and polyester media. This material is especially designed for back pulse operations, and offers enhanced stability and structural integrity. All cellulose blend filters are dimpled pleated. This pleat lock helps maintain pleat spacing during operation.



| | |
|------------------------|---------------------------------|
| Height: | 26" |
| Outside Diameter: | 13.865" |
| Inside Diameter: | 9.479" |
| Style: | Open on Both Ends |
| Gasket: | .5" x .5" Molded Natural Rubber |
| Pleat Count: | 355 |
| Pleat Depth: | 2" |
| Pleat Spacing: | Pleat lock |
| Filtration Area: | 256 Sqft |
| Filter Media: | FR Cell/Poly Blend |
| Inner Cage: | Galv. Expanded Metal 72% Open |
| Outer Cage: | Galv. Expanded Metal 72% Open |
| End Caps: | Galvanized Metal |
| Pleat/End Cap Bonding: | Urethane |
| Nominal Air Flow: | 500 cfm |
| Nominal Resistance: | 1.0" wg |
| Efficiency: | 99% @ .5 micron |
| Max. Operating Temp: | 180°F |



1915526100

