



TD3921526101-72483

Industrial-Maid

TF: 1-877-624-3247

351 S. 12th Rd.

Fax: 402-798-7117

8PP-72483-01

Cortland, Nebraska 68331 [www.industrial-maid.com](http://www.industrial-maid.com)

### FR Cellulose-Polyester Blend Cartridge

Industrial Maid’s filters are made from a premium blend of flame retardant cellulose and polyester. This material is especially designed for back pulse operations, and offers enhanced stability and structural integrity. All cellulose blend filters are dimpled pleated. This pleat lock helps maintain pleat spacing during operation.



|                      |                                  |
|----------------------|----------------------------------|
| Height:              | 26"                              |
| OD:                  | 12.74"                           |
| ID:                  | 8.38"                            |
| Style:               | Open/Closed with Bolt Hole       |
| Gasket               | Natural Rubber Gasket            |
| Pleat Count:         | 315                              |
| Pleat Depth:         | 2"                               |
| Pleat Spacing:       | Pleat lock                       |
| Filtration Area:     | 226 Sqft                         |
| Filter Media:        | FR Cell/Poly Blend               |
| Inner Cage:          | Galv. Expanded Metal 72% Open    |
| Outer Cage:          | Galv. Expanded Metal 72% Open    |
| Potting Material:    | Urethane                         |
| Nominal Air Flow:    | 500 cfm                          |
| Nominal Resistance:  | 1.0" wg                          |
| Efficiency:          | 99% @ .5Micron (see media guide) |
| Max. Operating Temp: | 180°F                            |



3921526101

