



Industrial-Maid
351 S. 12th Rd.
Cortland, Nebraska 68331

TF: 1-877-624-3247
Fax: 402-798-7117
www.industrial-maid.com

TR1778222101-251150001

251150001

FR Cell/Poly Blend Cartridge

Industrial Maid's filters are made from a premium blend of flame retardant cellulose and polyester. This material is especially designed for back pulse operations, and offers enhanced stability and structural integrity. All cellulose blend filters are dimpled pleated. This pleat lock helps maintain pleat spacing during operation.



Height:	21"
Outside Diameter:	17.25"
Inside Diameter:	12.75"
Style:	Open/Open
Gasket:	Gaskets On Both Ends
Pleat Count:	475
Pleat Depth:	2"
Pleat Spacing:	Pleat lock
Filtration Area:	272 Sq.ft.
Filter Media:	FR Cell/Poly Blend
Inner Cage:	Galv. Expanded Metal 72% Open
Outer Cage:	Galv. Expanded Metal 72% Open
End Caps:	Galvanized Metal
Pleat/End Cap Bonding:	Urethane
Nominal Air Flow:	500 cfm
Nominal Resistance:	1.0" wg
Efficiency:	99.5 @ .5 micron
Max. Operating Temp:	180°F
Shipping Weight	20 lbs



1778222101

