



Industrial-Maid
351 S. 12th Rd.
Cortland, Nebraska 68331

TF: 1-877-624-3247
Fax: 402-798-7117
www.industrial-maid.com

UAS1226926103-0320

Replaces UAS 33-0320

Industrial Maid’s filters feature a premium blend of flame retardant cellulose and polyester media. This material is especially designed for back pulse operations, and offers enhanced stability and structural integrity. All cellulose blend filters are dimpled pleated. This pleat lock helps maintain pleat spacing during operation.



Height:	26"
Outside Diameter:	12.75"
Inside Diameter:	8.3"
Style:	Open on Both Ends
Gasket:	.375" x .5 "Molded Natural Rubber
Pleat Count:	315
Pleat Depth:	2"
Pleat Spacing:	Pleat lock
Filtration Area:	226 Sq Ft
Filter Media:	FR Cell/Poly Blended Media
Inner Cage:	Galv. Expanded Metal 72% Open
Outer Support:	2 Outer Bands
End Caps:	Galvanized Metal
Pleat/End Cap Bonding:	Urethane
Nominal Air Flow:	500 cfm
Nominal Resistance:	1.0" wg
Efficiency:	99% @ .5 micron (ref media guide)
Max. Operating Temp:	180°F

1226926103

