



TD3921526101-191233

Industrial-Maid

TF: 1-877-624-3247

351 S. 12th Rd.

Fax: 402-798-7117

P191233-461-436

Cortland, Nebraska 68331 [www.industrial-maid.com](http://www.industrial-maid.com)

### FR Cellulose-Polyester Blend Cartridge

Industrial Maid’s filters are made from a premium blend of flame retardant cellulose and polyester. This material is especially designed for back pulse operations, and offers enhanced stability and structural integrity. All cellulose blend filters are dimpled pleated. This pleat lock helps maintain pleat spacing during operation.



Height:	26"
OD:	12.74"
ID:	8.38"
Style:	Open/Closed with Bolt Hole
Gasket	Natural Rubber Gasket
Pleat Count:	315
Pleat Depth:	2"
Pleat Spacing:	Pleat lock
Filtration Area:	226 Sqft
Filter Media:	FR Cell/Poly Blend
Inner Cage:	Galv. Expanded Metal 72% Open
Outer Cage:	Galv. Expanded Metal 72% Open
Potting Material:	Urethane
Nominal Air Flow:	500 cfm
Nominal Resistance:	1.0" wg
Efficiency:	99% @ .5Micron (see media guide)
Max. Operating Temp:	180°F



3921526101

